



| | | Type 33 Triple | | | |
|------|------|----------------|-------|-------|-------|
| L-mm | H-mm | 300 | 500 | 600 | 900 |
| 400 | kW | 0.712 | 1.091 | 1.264 | 1.723 |
| 500 | kW | 0.889 | 1.363 | 1.580 | 2.153 |
| 600 | kW | 1.067 | 1.636 | 1.895 | 2.584 |
| 700 | kW | 1.245 | 1.909 | 2.211 | 3.015 |
| 800 | kW | 1.423 | 2.181 | 2.527 | 3.445 |
| 900 | kW | 1.601 | 2.454 | 2.843 | 3.876 |
| 1000 | kW | 1.779 | 2.727 | 3.159 | 4.307 |
| 1100 | kW | 1.957 | 2.999 | 3.475 | 4.738 |
| 1200 | kW | 2.135 | 3.272 | 3.791 | 5.168 |
| 1400 | kW | 2.491 | 3.817 | 4.423 | 6.030 |
| 1600 | kW | 2.846 | 4.363 | 5.055 | 6.891 |
| 1800 | kW | 3.202 | 4.908 | 5.686 | 7.752 |
| 2000 | kW | 3.558 | 5.453 | 6.318 | 8.614 |
| 2300 | kW | 4.092 | 6.271 | 7.266 | |
| 2600 | kW | 4.625 | 7.089 | 8.214 | |
| 3000 | kW | 5.337 | 8.180 | 9.477 | |

TABLE BASED ON ΔT 60°C- MEAN WATER TEMPERATURE IN RADIATOR OF 80°C AND ROOM TEMPERATURE OF 20°C
 RADIATOR OUTPUTS TO EN442 STANDARD - NB: 400 HIGH SIZES AVAILABLE FOR ORDER (NOT EX STOCK)