

The energy experts The energy experts

Prepared for

PACIFIC ENERGY FIREPLACE PRODUCTS

PARTICULATE EMISSIONS, POWER OUTPUT AND EFFICIENCY TESTING OF THE NEO 1.6 INSERT SOLID FUEL APPLIANCE

Test Report No: HCMG/15/009
Issue Date: 6 March 2015
CONFIDENTIAL - CLIENT USE ONLY

by
S. Marland

© Copyright – (2015) HRL Limited

No part of this report may be reproduced by any process, stored in a retrieval system, transmitted nor disclosed to others without prior written permission of HRL Limited, except that the client may reproduce the report for its own internal use. The report is issued free of alterations and subject to the foregoing, may only be produced in full.

The results presented in this report relate exclusively to the samples selected by the client for the purpose of testing. No responsibility is taken for the representativeness of these samples.



Accredited for compliance with ISO/IEC 17025. This document will not be reproduced except in full. Accreditation # 561 Site # 3251

INITIAL DISTRIBUTION

	Copy No
Pacific Energy Fireplace Products 2975 Allenby Road Duncan BC V9L 6V8 CANADA	
Mr Ian Menzies	1
Pivot Stove & Heating Co. 238 Moorabool Street Geelong Vic 3220	
Mr Greg Parker-Hill	2
Mr Greg Parker-Hill (Copy for Certification)	3
HRL Technology Pty Ltd	
HRL Report Archive	4
File: 34147149	5

This is copy No

**PARTICULATE EMISSIONS POWER OUTPUT AND EFFICIENCY TESTING OF
THE NEO 1.6 INSERT SOLID FUEL APPLIANCE**

Report

The Neo 1.6 insert solid fuel appliance was tested for particulate emissions power output and efficiency according to the requirements of the joint Australian/New Zealand Standard AS/NZS 4012/4013 (2014).

The appliance particulate emissions factor was 1.1g/kg of hardwood that complies to AS/NZS 4014.1, and the average efficiency of the appliance for all burn rates was 67%.

The Neo 1.6 insert solid fuel appliance complies with the requirements of AS/NZS 4012/4013 (2014).

Investigation: A. Wood, A Reid & S. Marland

Report: S. Marland

Checked by: A. Reid

Signed:.....
A. Reid
Technical Officer

Approved:.....
S. Marland
Group Leader, Energy & Greenhouse Div. Morwell

1. INTRODUCTION

HRL Technology was requested to assess the Neo 1.6 insert solid fuel burning appliance. Particulate emissions power output and efficiency testing was performed according to the joint Australian/New Zealand Standards (AS/NZS) 4012/4013.

This report provides details of the tests performed at the Solid Fuel Heater Testing and Research Laboratory of HRL Technology, Morwell. The test program was conducted from January 26 to 30, 2015 by Mr A. Reid & Mr S. Marland. The testing was commissioned by Pacific Energy Frieplace Products and the test results remain the property of this company.

The appliance was tested using hardwood as the test fuel. This test fuel was used after conforming to the requirements of the joint AS/NZS 4014.1 (1999).

2. DETAILS OF APPLIANCE

The test results reported below apply only to the appliance model tested. The details of the appliance given in this section include features which may affect particulate emissions and thermal efficiency results. Any change in the construction or design of this appliance model could invalidate this report. Engineering diagrams were sighted and checked with HRL Technology internal test appliance measurements (joint AS/NZS 4013 Paragraph 8.2 [d]).

Appendix 1 gives appliance construction details.

3. INSTALLATION OF THE APPLIANCE

The appliance firebox was measured according to the method described in the joint AS/NZS 4012. The appliance fuel load, fuel length and number of wood pieces were then calculated. The appliance was burnt for at least 16 hours (two x 8 hours) to fully cure appliance paint and reduce firebrick moisture content.

Testing was conducted according to the manufacturer's verbal instructions (joint AS/NZS 4013 Paragraph 8.20[c]).

The test fuel was loaded according to the manufacturer's instructions. The appliance was operated initially with a small amount of fuel, and when the bed of embers was 24-26% of the single fuel load, the scale was tared and a pre-burn cycle was commenced. The calorimeter room and associated test equipment and sample weighing method are described in Appendix 2. The emissions test equipment and sample weighing method are described in Appendix 3. Appendix 4 shows photographs of a typical fuel load and the appliance under test.

3.1 High Burn Cycles

The appliance was fully fired in accordance with Section 6.3(a) of the joint AS/NZS 4012.

The average fuel load for initiating High Burn Cycles was 7.3kg. The primary air slide was fully open for each high burn cycle.

The appliance fan was set to High Auto.

3.2 Low Burn Cycles

The appliance was fired in accordance with Section 6.3(b) of the joint AS/NZS 4012.

The average fuel load for initiating Low Burn Cycles was 7.2kg. The first 20% of the test fuel mass was burnt with the primary air slide fully open (as per High Burn Cycles). The primary air slide was then reduced to an opening of 20mm. This is the minimum air slide setting.

The appliance fan was set to High Auto.

3.3 Medium Burn Cycles

The appliance was fired in accordance with Section 6.3(c) of the joint AS/NZS 4012.

The average fuel load for initiating Medium Burn Cycles was 7.3kg. The first 20% of the test fuel mass was burnt with the primary slide fully open (as per High Burn Cycles). The primary air slide was then reduced to an opening of 30mm.

The appliance fan was set to High Auto.

3.4 Test Fuel

The appliance was fired using hardwood with an average moisture content of 14.8% as the test fuel. Each cylindrical firewood piece was 191 ± 10 mm long with a diameter of between 75 mm and 110 mm. Seven pieces of wood were used for each test cycle. The average density of the hardwood was 0.85kg/l (dry basis). The specific energy of the hardwood was 20.73MJ/kg (oven dry basis). The ash content of the hardwood was 0.3% (dry basis).

4. RESULTS

4.1 Uncertainty of Measurement Statement

- a) The uncertainty of temperature measurement during the entire test period was $\pm 2.2^{\circ}\text{C}$ (at the 95% confidence level).
- b) The uncertainty of power measurement was $\pm 4.6\%$.
- c) The uncertainty of the outlet air pressure was ± 0.2 Pa.
- d) The uncertainty of the dilution tunnel pressure was ± 1 Pa.
- e) The uncertainty of particulate emission weights was ± 0.4 mg.
- f) The uncertainty of acetone dish and “O” ring weights was ± 1 mg.
- g) The uncertainty of the test fuel mass was ± 20 gm (on appliance balance).

4.2 Leak Test Results

The appliance passed the post-conditioning air flow test with a flue velocity of $0.3\text{m}^3/\text{min}$ at 25 Pa ($<1\text{ m}^3/\text{min}$ required in Standard).

The appliance passed the post-burn air flow test with a flue velocity of $0.4\text{m}^3/\text{min}$ at 25 Pa ($<1\text{ m}^3/\text{min}$ required in Standard).

The appliance conforms with clause 6.10 of AS/NZS 4012 (2014)

4.3 Operating Conditions

Table 1 shows the operating conditions for the appliance.

4.4 Efficiency/Power Results

Table 2 shows the power efficiency results for the appliance. Table 3 shows a summary of average power, dry fuel consumption rate and burn time for each burn cycle. The average efficiency for all burn cycles was 67%.

4.5 Particulate Emissions Factor

Table 4 shows the particulate emissions values for each burn cycle and the resultant appliance particulate emission factor of $1.1\text{g}/\text{kg}$ of hardwood that complies to AS/NZS 4014.1.

5. CONCLUSION

The Neo 1.6 insert solid fuel burning appliance produced an appliance particulate emissions factor of 1.1g/kg and an average efficiency of 67% for all burn rates, using hardwood that complies to AS/NZS 4014.1, when tested according to joint AS/NZS 4012, AS/NZS 4013 (2014).

The Neo 1.6 insert solid fuel burning appliance complies with the requirement of a combined efficiency of greater than 55% and a particulate emissions factor of not greater than 2.5g/kg of hardwood that complies to AS/NZS4014.1 in AS/NZS4012 (2014) and AS/NZS4013 (2014).

Table 1: Operating Conditions for the Neo 1.6 insert Solid Fuel Appliance

CONDITION	COMMENTS
Fire Box Volume	44 Litres
Wood Type	Hardwood (Redgum)
Number of Wood Pieces	7
Length of Wood Pieces	191mm
Method of Loading	3 on 4, front to rear
Fan/Fan Speed	High Auto for all burn cycles

Table 3: Summary of Average Power, Combined Efficiency, Burn Rate and Burn Time

Primary Air Settings	Average Power (kW)	Average Peak Power (kW)	Efficiency (%)	Average Dry Fuel Consumption Rate (kg/hr)	Average Burn Time (mins)
High	7.7	12.1	62	2.1	173
Medium	6.8		67	1.8	211
Low	5.9		73	1.4	261

Appliance Combined Efficiency = 67%.

Table 4: Particulate Emissions for the Neo 1.6 insert Solid Fuel Appliance

Primary Air Setting	Total Emission Weight (mg)	Sample Dilution Tunnel Ratio	Particulate Emission Factor (g/kg) Oven Dry Wood
High No 1	5.3	1084.6	0.9
High No 2	5.5	1079.5	1.0
High No 3	8.4	1069.2	1.5
Average			1.1
Medium No 1	6.4	1077.7	1.1
Medium No 2	6.7	1063.8	1.1
Medium No 3	7.5	1063.2	1.3
Average			1.2
Low No 1	3.7	1075.9	0.7
Low No 2	8.5	1086.5	1.5
Low No 3	6.7	1071.4	1.2
Average			1.1

Appliance Particulate Emissions Factor = 1.1g/kg (oven dry hardwood).

Table 2: Power Efficiency of the Neo 1.6 insert Solid Fuel Appliance

Primary Air Setting	Commencement Time/Date	Cycle Time (mins)	Average Power (kW)	Wet Wood Mass (kg)	Wood Moisture Content (wt%)	Power Efficiency (%)	Peak Power (kW)	Dry Fuel Consumption Rate (kg/hr)
High No 1	20:05 27/01/2015	172	8.33	7.33	15.1	66.7	12.69	2.17
High No 2	00:19 28/01/2015	158	8.00	7.27	15.9	59.9	11.74	2.32
High No 3	03:14 28/01/2015	190	6.69	7.16	15.4	60.7	11.95	1.91
Medium No 1	23:27 29/01/2015	206	6.79	7.15	12.6	64.8		1.84
Medium No 2	02:54 30/01/2015	218	7.01	7.34	15.5	71.3		1.71
Medium No 3	06:33 30/01/2015	210	6.47	7.26	15.5	64.0		1.75
Low No 1	19:49 28/01/2015	254	6.04	7.23	16.0	73.2		1.43
Low No 2	05:56 29/01/2015	254	5.69	7.20	15.5	68.7		1.44
Low No 3	15:06 29/01/2015	274	6.11	7.09	12.1	77.8		1.36

**APPENDIX 1:
SOLID FUEL BURNING APPLIANCE CONSTRUCTION DETAILS**

Appliance Model Name:	<i>Neo 1.6 Insert</i>		
Manufacturer:	Pacific Energy Fireplace Products		
Serial Number:	40310763		
Insert Width:	545mm		
Insert Depth:	433mm		
Insert Height:	517mm		
Firebox Description:	<i>Height: 300mm</i>	<i>Width: 465mm</i>	<i>Depth: 288mm</i>
Firebox Material Type/ Seam Fully Welded:	3.5mm steel, seams fully welded		
Firebrick Size:	Firebox is fully lined with bricks		
Main Door Opening:	<i>Height: 282mm</i>	<i>Width: 434mm</i>	
Door:	<i>Height: 373mm</i>	<i>Width: 515mm</i>	<i>Depth: 38mm (max)</i>
Door Glass:	<i>Height: 247mm</i>	<i>Width: 390mm</i>	
Primary Air Location:	Under firebox		
Dimension of Primary Air:	3 holes 1 @ 9.0mm dia + 1 @ 20mm dia + half circle @ 39mm		
Area of Primary (mm ²)	975mm ²		
Secondary/Tertiary Air Location:	Incorporated into baffle plate		
Dimension of Secondary/Tertiary Air:	24 holes @ 4mm dia + 18 holes @ 5.0mm dia + 12 holes @ 6.5mm dia		
Area of Secondary/Tertiary Air (mm ²):	361mm ²		
Flue Dimensions:	152mm OD		
Spigot Dimensions:	160mm OD	153mm ID	
Spigot to Rear of Appliance:	61mm		
Rear Internal to External Heat Shield:	50mm		
Side Internal to External Heat Shield:	55-100mm		
Heat Shield Material Type:	1.5mm steel		
Water Heater Fitted:	NO		
Fan Location/Speeds:	Variable speed with thermostat control		
Catalytic Combustor:	NO		
Grate:	No		
Diagrams:	Over the page		
<p>Note the accuracy of measurements in Appendix 2 are $\pm 5\%$ of the recorded value</p> <p>Signed: <i>A. Reed</i> Date: <i>10/3/15</i></p>			

APPENDIX 2: CALORIMETER ROOM

The HRL Technology Pty Ltd calorimetry room is an insulated room (75 mm thick polystyrene lined on walls, floor and ceiling) of internal dimensions 3.0 m x 3.0 m x 2.4 m high.

Air flow into the room is through a 300 mm diameter duct from a manually controlled variable speed fan. Air flow out of the room is via a 300 mm diameter duct also connected to a variable speed fan. Both inlet and outlet air fans are connected to the same speed controller. A baffle over the air entry into the inlet fan controls calorimetry room pressure (equivalent with external room pressure).

Air flow temperatures are measured by three type K thermocouples in both the inlet and outlet ducts. Air velocity of the outlet is measured by a pitot tube connected to a NATA certified inclined manometer.

The solid fuel appliance sits on Mercury 0 –300 kg digital scales. The flue system consists of an insulated silicone oil bath that isolates the weight of the stove from the remainder of the flue. The flue, where it exits from the room, passes into an insulated flue casing. Total flue length above the top of the scales is set at 4.6 ± 0.1 m.

Temperatures and transducer signals are fed to a Data Electronic DT500 data logger that is connected to a personal computer. A digital signal from the scales is also sent to the computer.

The calorimeter room heat losses through the walls have been measured from electrical resistance heaters of known output.

During operation, airflow into the room is adjusted to maintain the air pressure in the room at atmospheric pressure (baffle over inlet air). Data is collected from thermocouples, air flow and scales weight and dry gas flow rate every two minutes.

APPENDIX 3: EMISSIONS TEST EQUIPMENT AND SAMPLE WEIGHING METHOD

The emissions equipment consists of a dilution tunnel including collection hood, pitot tube and NATA certified inclined manometer for air flow measurement, sampling train and an in-line variable speed centrifugal extraction fan.

The sampling train consists of a sample probe, double filter assembly, including thermocouple gas drier, vacuum pump, dry gas meter and flow meter (pulsed light 5 pulses/litre).

Forty-seven millimetre glass fibre filters (ex Gelman Sciences) that have been weighed are mounted in the filter assembly.

Data from thermocouples, transducer and dry gas meter is fed to a Data Electronic DT500 data logger that is connected to a personal computer. This information is collected at the same time as data from the calorimeter room.

Towards the end of the pre-burn cycle (>10 minutes before end of pre-burn cycle) the dilution tunnel extraction fan is turned on and the dilution tunnel hood is swung over the appliance flue.

When a new cycle commences, the sample vacuum pump turns on automatically until the end of the cycle when the sample pump automatically stops once <0.05 kg test fuel mass is detected. Sample flow rate and dilution tunnel flow rate is manually controlled within specified ranges.

Sample flow rate is measured by a 1 litre/rev dry gas meter which is coupled to the computer by means of a light detector giving a pulsed output.

At the completion of a burn cycle, the filters are removed from the filter holders and placed in a desiccator for drying. Condensed and entrapped emissions from the sample probe are washed with acetone into a glass beaker. A rifle cleaning rod is used to clean the inside of the sampling probe. The cleaning rod is then washed with acetone (into the glass beaker). The acetone washing is allowed to vaporise to dryness and the residue weight determined. The two dried filters are reweighed.

Emission weight is then determined by totalling the filter weight increases from the two filters and the residue from acetone washings.

APPENDIX 4:

Photograph 1: Appliance Under Test



Photograph 2: Test Fuel Load

